

# OpenHPC (v1.3.2) Cluster Building Recipes

---

CentOS7.3 Base OS

Warewulf/SLURM Edition for Linux\* (aarch64)

---

# [ Tech Preview ]

Document Last Update: 2017-09-07

Document Revision: 8431212

## Legal Notice

Copyright © 2016-2017, OpenHPC, a Linux Foundation Collaborative Project. All rights reserved.



This documentation is licensed under the Creative Commons Attribution 4.0 International License. To view a copy of this license, visit <http://creativecommons.org/licenses/by/4.0>.

Intel, the Intel logo, and other Intel marks are trademarks of Intel Corporation in the U.S. and/or other countries.  
\*Other names and brands may be claimed as the property of others.

## Contents

|          |  |           |
|----------|--|-----------|
| <b>1</b> | <b>Tech Preview</b>                                    | <b>5</b>  |
| <b>2</b> | <b>Introduction</b>                                    | <b>5</b>  |
| 2.1      | Target Audience  | 6         |
| 2.2      | Requirements/Assumptions                               | 6         |
| 2.3      | Inputs   | 7         |
| <b>3</b> | <b>Install Base Operating System (BOS)</b>             | <b>8</b>  |
| <b>4</b> | <b>Install OpenHPC Components</b>                      | <b>8</b>  |
| 4.1      | Enable OpenHPC repository for local use                | 8         |
| 4.2      | Installation template                                  | 9         |
| 4.3      | Add provisioning services on <i>master</i> node        | 9         |
| 4.4      | Add resource management services on <i>master</i> node | 10        |
| 4.5      | Add InfiniBand support services on <i>master</i> node  | 10        |
| 4.6      | Complete basic Warewulf setup for <i>master</i> node   | 11        |
| 4.7      | Define <i>compute</i> image for provisioning           | 11        |
| 4.7.1    | Build initial BOS image                                | 12        |
| 4.7.2    | Add OpenHPC components                                 | 12        |
| 4.7.3    | Customize system configuration                         | 13        |
| 4.7.4    | Additional Customization ( <i>optional</i> )           | 13        |
| 4.7.4.1  | Increase locked memory limits                          | 14        |
| 4.7.4.2  | Enable ssh control via resource manager                | 14        |
| 4.7.4.3  | Add Lustre client                                      | 14        |
| 4.7.4.4  | Enable forwarding of system logs                       | 16        |
| 4.7.4.5  | Add Nagios monitoring                                  | 16        |
| 4.7.4.6  | Add Ganglia monitoring                                 | 18        |
| 4.7.4.7  | Add ClusterShell                                       | 18        |
| 4.7.4.8  | Add <i>mrsh</i>  | 19        |
| 4.7.4.9  | Add <i>genders</i>                                     | 19        |
| 4.7.4.10 | Add ConMan   | 19        |
| 4.7.5    | Import files   | 20        |
| 4.8      | Finalizing provisioning configuration                  | 20        |
| 4.8.1    | Assemble bootstrap image                               | 20        |
| 4.8.2    | Assemble Virtual Node File System (VNFS) image         | 20        |
| 4.8.3    | Register nodes for provisioning                        | 21        |
| 4.8.4    | Optional kernel arguments                              | 22        |
| 4.8.5    | Optionally configure stateful provisioning             | 23        |
| 4.9      | Boot compute nodes                                     | 23        |
| <b>5</b> | <b>Install OpenHPC Development Components</b>          | <b>24</b> |
| 5.1      | Development Tools                                      | 24        |
| 5.2      | Compilers  | 24        |
| 5.3      | MPI Stacks   | 25        |
| 5.4      | Performance Tools                                      | 25        |
| 5.5      | Setup default development environment                  | 25        |
| 5.6      | 3rd Party Libraries and Tools                          | 25        |
| <b>6</b> | <b>Resource Manager Startup</b>                        | <b>26</b> |

|                   |  |           |
|-------------------|--|-----------|
| <b>7</b>          | <b>Run a Test Job</b>                                    | <b>27</b> |
| 7.1               | Interactive execution . . . . .                          | 27        |
| 7.2               | Batch execution . . . . .                                | 29        |
| <b>Appendices</b> |  | <b>30</b> |
| A                 | Installation Template . . . . .                          | 30        |
| B                 | Upgrading OpenHPC Packages . . . . .                     | 31        |
| B.1               | New component variants . . . . .                         | 31        |
| C                 | Integration Test Suite . . . . .                         | 33        |
| D                 | Customization . . . . .                                  | 35        |
| D.1               | Adding local Lmod modules to OpenHPC hierarchy . . . . . | 35        |
| D.2               | Rebuilding Packages from Source . . . . .                | 36        |
| E                 | Package Manifest . . . . .                               | 37        |
| F                 | Package Signatures . . . . .                             | 46        |

## 1 Tech Preview

This guide highlights the initial availability of OpenHPC packages targeted for use on 64-bit ARM-based architectures. This collection is being provided as a **Tech Preview** release initially, as there are some known issues around provisioning and a subset of development packages. A running log of errata and fixes can be found at the [ARM Tech Preview Wiki](#).

The guide follows the general installation steps laid out in other companion OpenHPC recipes. However, the provisioning steps as outlined with Warewulf (most of the steps in § 4.3 thru 4.9) are not directly usable without additional modification to the PXE boot process. Consequently, users interested in leveraging packages from this Tech Preview are encouraged to enable the repo (see § 4.1) and install desired development components (§ 5) on top of systems where the underlying base OS is pre-installed. In addition, if multiple nodes are available, the SLURM resource manager can be used to schedule resources. Future OpenHPC releases will expand on this tech preview to include validated recipes for a bare-metal cluster install.

Known Package Issues:

- **GSL:** a small subset of tests performed with the GSL library failed precision related tests. This is currently attributed to the fact that the tests included in GSL are tuned for x86 which does 80-bit extended precision.
- **PAPI:** hardware counter availability may not be available depending on the underlying ARM platform.
- **MPI:** The hardware used for validating this Tech Preview release contained only ethernet. The available MPI stacks reflect this test environment.
- **Hypre and SuperLU-dist:** the libraries build, but when linking test applications unresolved symbols remain
- **Nagios and Ganglia:** don't work on SLES-12-SP2 due to missing PHP5 dependencies
- **Lustre:** since various ARM platforms require different kernels than the standard ones provided by the SLES-12-SP2 and CentOS-7.3 distributions, building a lustre client that would work for these specific platform configurations was beyond the scope of this release.
- **Warewulf:** the ARM Standard Base Boot Requirements and Standard Base System Architecture requires specific UEFI support during the boot process which doesn't seem to be compatible with the way warewulf currently auto-provisions worker nodes. There is a work-around, but it requires some manual intervention during installation and deployment of the nodes.

## 2 Introduction

This guide presents a simple cluster installation procedure using components from the OpenHPC software stack. OpenHPC represents an aggregation of a number of common ingredients required to deploy and manage an HPC Linux\* cluster including provisioning tools, resource management, I/O clients, development tools, and a variety of scientific libraries. These packages have been pre-built with HPC integration in mind while conforming to common Linux distribution standards. The documentation herein is intended to be reasonably generic, but uses the underlying motivation of a small, 4-node stateless cluster installation to define a step-by-step process. Several optional customizations are included and the intent is that these collective instructions can be modified as needed for local site customizations.

**Base Linux Edition:** this edition of the guide highlights installation without the use of a companion configuration management system and directly uses distro-provided package management tools for component selection. The steps that follow also highlight specific changes to system configuration files that are required as part of the cluster install process.

## 2.1 Target Audience

This guide is targeted at experienced Linux system administrators for HPC environments. Knowledge of software package management, system networking, and PXE booting is assumed. Command-line input examples are highlighted throughout this guide via the following syntax:

```
[sms]# echo "OpenHPC hello world"
```

Unless specified otherwise, the examples presented are executed with elevated (root) privileges. The examples also presume use of the BASH login shell, though the equivalent commands in other shells can be substituted. In addition to specific command-line instructions called out in this guide, an alternate convention is used to highlight potentially useful tips or optional configuration options. These tips are highlighted via the following format:

Tip

Any sufficiently advanced technology is indistinguishable from magic. –Arthur C. Clarke

## 2.2 Requirements/Assumptions

This installation recipe assumes the availability of a single head node *master*, and four *compute* nodes. The *master* node serves as the overall system management server (SMS) and is provisioned with CentOS7.3 and is subsequently configured to provision the remaining *compute* nodes with Warewulf in a stateless configuration. The terms *master* and SMS are used interchangeably in this guide. For power management, we assume that the compute node baseboard management controllers (BMCs) are available via IPMI from the chosen master host. For file systems, we assume that the chosen master server will host an NFS file system that is made available to the compute nodes. Installation information is also discussed to optionally include a Lustre file system mount and in this case, the Lustre file system is assumed to exist previously.




Figure 1: Overview of physical cluster architecture.

An outline of the physical architecture discussed is shown in Figure 1 and highlights the high-level

networking configuration. The *master* host requires at least two Ethernet interfaces with *eth0* connected to the local data center network and *eth1* used to provision and manage the cluster backend (note that these interface names are examples and may be different depending on local settings and OS conventions). Two logical IP interfaces are expected to each compute node: the first is the standard Ethernet interface that will be used for provisioning and resource management. The second is used to connect to each host's BMC and is used for power management and remote console access. Physical connectivity for these two logical IP networks is often accommodated via separate cabling and switching infrastructure; however, an alternate configuration can also be accommodated via the use of a shared NIC, which runs a packet filter to divert management packets between the host and BMC.

In addition to the IP networking, there is a high-speed network (InfiniBand in this recipe) that is also connected to each of the hosts. This high speed network is used for application message passing and optionally for Lustre connectivity as well.

## 2.3 Inputs

As this recipe details installing a cluster starting from bare-metal, there is a requirement to define IP addresses and gather hardware MAC addresses in order to support a controlled provisioning process. These values are necessarily unique to the hardware being used, and this document uses variable substitution (`${variable}`) in the command-line examples that follow to highlight where local site inputs are required. A summary of the required and optional variables used throughout this recipe are presented below. Note that while the example definitions above correspond to a small 4-node compute subsystem, the compute parameters are defined in array format to accommodate logical extension to larger node counts.

|  |   |
|--|---|
| • <code>\${sms_name}</code>                      | # Hostname for SMS server                           |
| • <code>\${sms_ip}</code>                        | # Internal IP address on SMS server                 |
| • <code>\${sms_eth_internal}</code>              | # Internal Ethernet interface on SMS                |
| • <code>\${eth_provision}</code>                 | # Provisioning interface for computes               |
| • <code>\${internal_netmask}</code>              | # Subnet netmask for internal network               |
| • <code>\${ntp_server}</code>                    | # Local ntp server for time synchronization         |
| • <code>\${bmc_username}</code>                  | # BMC username for use by IPMI                      |
| • <code>\${bmc_password}</code>                  | # BMC password for use by IPMI                      |
| • <code>\${num_computes}</code>                  | # Total # of desired compute nodes                  |
| • <code>\${c_ip[0]}, \${c_ip[1]}, ...</code>     | # Desired compute node addresses                    |
| • <code>\${c_bmc[0]}, \${c_bmc[1]}, ...</code>   | # BMC addresses for computes                        |
| • <code>\${c_mac[0]}, \${c_mac[1]}, ...</code>   | # MAC addresses for computes                        |
| • <code>\${c_name[0]}, \${c_name[1]}, ...</code> | # Host names for computes                           |
| • <code>\${compute_regex}</code>                 | # Regex matching all compute node names (e.g. "c*") |
| • <code>\${compute_prefix}</code>                | # Prefix for compute node names (e.g. "c")          |

Optional:

|  |                                      |
|--|--------------------------------------|
| • <code>\${sysmgmt_host}</code>                    | # BeeGFS System Management host name |
| • <code>\${mgs_fs_name}</code>                     | # Lustre MGS mount name              |
| • <code>\${sms_ipoib}</code>                       | # IPoIB address for SMS server       |
| • <code>\${ipoib_netmask}</code>                   | # Subnet netmask for internal IPoIB  |
| • <code>\${c_ipoib[0]}, \${c_ipoib[1]}, ...</code> | # IPoIB addresses for computes       |
| • <code>\${kargs}</code>                           | # Kernel boot arguments              |

### 3 Install Base Operating System (BOS)

In an external setting, installing the desired BOS on a *master* SMS host typically involves booting from a DVD ISO image on a new server. With this approach, insert the CentOS7.3 DVD, power cycle the host, and follow the distro provided directions to install the BOS on your chosen *master* host. Alternatively, if choosing to use a pre-installed server, please verify that it is provisioned with the required CentOS7.3 distribution.

Prior to beginning the installation process of OpenHPC components, several additional considerations are noted here for the SMS host configuration. First, the installation recipe herein assumes that the SMS host name is resolvable locally. Depending on the manner in which you installed the BOS, there may be an adequate entry already defined in `/etc/hosts`. If not, the following addition can be used to identify your SMS host.

```
[sms]# echo ${sms_ip} ${sms_name} >> /etc/hosts
```

While it is theoretically possible to enable SELinux on a cluster provisioned with Warewulf, doing so is beyond the scope of this document. Even the use of permissive mode can be problematic and we therefore recommend disabling SELinux on the *master* SMS host. If SELinux components are installed locally, the `selinuxenabled` command can be used to determine if SELinux is currently enabled. If enabled, consult the distro documentation for information on how to disable.

Finally, provisioning services rely on DHCP, TFTP, and HTTP network protocols. Depending on the local BOS configuration on the SMS host, default firewall rules may prohibit these services. Consequently, this recipe assumes that the local firewall running on the SMS host is disabled. If installed, the default firewall service can be disabled as follows:

```
[sms]# systemctl disable firewalld
[sms]# systemctl stop firewalld
```

## 4 Install OpenHPC Components

With the BOS installed and booted, the next step is to add desired OpenHPC packages onto the *master* server in order to provide provisioning and resource management services for the rest of the cluster. The following subsections highlight this process.

### 4.1 Enable OpenHPC repository for local use

To begin, enable use of the OpenHPC repository by adding it to the local list of available package repositories. Note that this requires network access from your *master* server to the OpenHPC repository, or alternatively, that the OpenHPC repository be mirrored locally. In cases where network external connectivity is available, OpenHPC provides an `ohpc-release` package that includes GPG keys for package signing and repository enablement. The example which follows illustrates installation of the `ohpc-release` package directly from the OpenHPC build server.

```
[sms]# yum install http://build.openhpc.community/OpenHPC:/1.3/CentOS_7/aarch64/ohpc-release-1.3-1.el7.aarch64.rpm
```

### Tip

Many sites may find it useful or necessary to maintain a local copy of the OpenHPC repositories. To facilitate this need, standalone tar archives are provided – one containing a repository of binary packages as well as any available updates, and one containing a repository of source RPMS. The tar files also contain a simple bash script to configure the package manager to use the local repository after download. To use, simply unpack the tarball where you would like to host the local repository and execute the `make_repo.sh` script. Tar files for this release can be found at <http://build.openhpc.community/dist/1.3.2>

In addition to the OpenHPC package repository, the *master* host also requires access to the standard base OS distro repositories in order to resolve necessary dependencies. For CentOS7.3, the requirements are to have access to both the base OS and EPEL repositories for which mirrors. Note that for this Tech Preview, an altarch variation of the CentOS\_7.3 release was used. Additional info and a pointer to available ISO images is available at the links below:

- CentOS Alt Arch Info ([aarch64](#))
- Repository/ISO images ([7.3.1611](#))

## 4.2 Installation template

The collection of command-line instructions that follow in this guide, when combined with local site inputs, can be used to implement a bare-metal system installation and configuration. The format of these commands is intended to be usable via direct cut and paste (with variable substitution for site-specific settings). Alternatively, the OpenHPC documentation package (`docs-ohpc`) includes a template script which includes a summary of all of the commands used herein. This script can be used in conjunction with a simple text file to define the local site variables defined in the previous section (§ 2.3) and is provided as a convenience for administrators. For additional information on accessing this script, please see Appendix A.

## 4.3 Add provisioning services on *master* node

With the OpenHPC repository enabled, we can now begin adding desired components onto the *master* server. This repository provides a number of aliases that group logical components together in order to help aid in this process. For reference, a complete list of available group aliases and RPM packages available via OpenHPC are provided in Appendix E. To add support for provisioning services, the following commands illustrate addition of a common base package followed by the Warewulf provisioning system.

```
# Install base meta-packages
[sms]# yum -y install ohpc-base
[sms]# yum -y install ohpc-warewulf
```

### Tip

Many server BIOS configurations have PXE network booting configured as the primary option in the boot order by default. If your compute nodes have a different device as the first in the sequence, the `ipmitool` utility can be used to enable PXE.

```
[sms]# ipmitool -E -I lanplus -H ${bmc_ipaddr} -U root chassis bootdev pxe options=persistent
```

HPC systems rely on synchronized clocks throughout the system and the NTP protocol can be used to facilitate this synchronization. To enable NTP services on the SMS host with a specific server `${ntp_server}`, issue the following:

```
[sms]# systemctl enable ntpd.service
[sms]# echo "server ${ntp_server}" >> /etc/ntp.conf
[sms]# systemctl restart ntpd
```

## 4.4 Add resource management services on *master* node

OpenHPC provides multiple options for distributed resource management. The following command adds the Slurm workload manager server components to the chosen *master* host. Note that client-side components will be added to the corresponding compute image in a subsequent step.

```
# Install slurm server meta-package
[sms]# yum -y install ohpc-slurm-server

# Identify resource manager hostname on master host
[sms]# perl -pi -e "s/ControlMachine=\S+/ControlMachine=${sms_name}/" /etc/slurm/slurm.conf
```

### Tip

SLURM requires enumeration of the physical hardware characteristics for compute nodes under its control. In particular, three configuration parameters combine to define consumable compute resources: *Sockets*, *CoresPerSocket*, and *ThreadsPerCore*. The default configuration file provided via OpenHPC assumes dual-socket, 8 cores per socket, and two threads per core for this 4-node example. If this does not reflect your local hardware, please update the configuration file at `/etc/slurm/slurm.conf` accordingly to match your particular hardware.

Other versions of this guide are available that describe installation of other resource management systems, and they can be found in the `docs-ohpc` package.

## 4.5 Add InfiniBand support services on *master* node

The following command adds OFED and PSM support using base distro-provided drivers to the chosen *master* host.

```
[sms]# yum -y groupinstall "InfiniBand Support"
[sms]# yum -y install infinipath-psm

# Load IB drivers
[sms]# systemctl start rdma
```

### Tip

InfiniBand networks require a subnet management service that can typically be run on either an administrative node, or on the switch itself. The optimal placement and configuration of the subnet manager is beyond the scope of this document, but CentOS7.3 provides the `opensm` package should you choose to run it on the *master* node.

With the InfiniBand drivers included, you can also enable (optional) IPoIB functionality which provides a mechanism to send IP packets over the IB network. If you plan to mount a Lustre file system over InfiniBand (see §4.7.4.3 for additional details), then having IPoIB enabled is a requirement for the Lustre client. OpenHPC provides a template configuration file to aid in setting up an *ib0* interface on the *master* host. To use, copy the template provided and update the `${sms_ipoib}` and `${ipoib_netmask}` entries to match local desired settings (alter *ib0* naming as appropriate if system contains dual-ported or multiple HCAs).

```
[sms]# cp /opt/ohpc/pub/examples/network/centos/ifcfg-ib0 /etc/sysconfig/network-scripts

# Define local IPoIB address and netmask
[sms]# perl -pi -e "s/master_ipoib/${sms_ipoib}/" /etc/sysconfig/network-scripts/ifcfg-ib0
[sms]# perl -pi -e "s/ipoib_netmask/${ipoib_netmask}/" /etc/sysconfig/network-scripts/ifcfg-ib0

# Initiate ib0
[sms]# ifup ib0
```

## 4.6 Complete basic Warewulf setup for *master* node

At this point, all of the packages necessary to use Warewulf on the *master* host should be installed. Next, we need to update several configuration files in order to allow Warewulf to work with CentOS7.3 and to support local provisioning using a second private interface (refer to Figure 1).

### Tip

By default, Warewulf is configured to provision over the `eth1` interface and the steps below include updating this setting to override with a potentially alternatively-named interface specified by `${sms_eth_internal}`.

```
# Configure Warewulf provisioning to use desired internal interface
[sms]# perl -pi -e "s/device = eth1/device = ${sms_eth_internal}/" /etc/warewulf/provision.conf

# Enable tftp service for compute node image distribution
[sms]# perl -pi -e "s/^\s+disable\s+= yes/ disable = no/" /etc/xinetd.d/tftp

# Enable internal interface for provisioning
[sms]# ifconfig ${sms_eth_internal} ${sms_ip} netmask ${internal_netmask} up

# Restart/enable relevant services to support provisioning
[sms]# systemctl restart xinetd
[sms]# systemctl enable mariadb.service
[sms]# systemctl restart mariadb
[sms]# systemctl enable httpd.service
[sms]# systemctl restart httpd
[sms]# systemctl enable dhcpd.service
```

## 4.7 Define *compute* image for provisioning

With the provisioning services enabled, the next step is to define and customize a system image that can subsequently be used to provision one or more *compute* nodes. The following subsections highlight this process.

### 4.7.1 Build initial BOS image

The OpenHPC build of Warewulf includes specific enhancements enabling support for CentOS7.3. The following steps illustrate the process to build a minimal, default image for use with Warewulf. We begin by defining a directory structure on the *master* host that will represent the root filesystem of the compute node. The default location for this example is in `/opt/ohpc/admin/images/centos7.3`.

#### Tip

Warewulf is configured by default to access an external repository (`mirror.centos.org`) during the `wmmkchroot` process. If the master host cannot reach the public CentOS mirrors, or if you prefer to access a locally cached mirror, set the `YUM_MIRROR` environment variable to your desired repo location *prior* to running the `wmmkchroot` command below. For example:

```
# Override default OS repository (optional) - set YUM_MIRROR variable to desired repo location
[sms]# export YUM_MIRROR=${BOS_MIRROR}
```

```
# Define chroot location
[sms]# export CHROOT=/opt/ohpc/admin/images/centos7.3

# Build initial chroot image
[sms]# wmmkchroot centos-7 $CHROOT
```

### 4.7.2 Add OpenHPC components

The `wmmkchroot` process used in the previous step is designed to provide a minimal CentOS7.3 configuration. Next, we add additional components to include resource management client services, InfiniBand drivers, and other additional packages to support the default OpenHPC environment. This process augments the chroot-based install performed by `wmmkchroot` to modify the base provisioning image and will access the BOS and OpenHPC repositories to resolve package install requests. We begin by installing a few common base packages:

```
# Install compute node base meta-package
[sms]# yum -y --installroot=$CHROOT install ohpc-base-compute
```

To access the remote repositories by hostname (and not IP addresses), the chroot environment needs to be updated to enable DNS resolution. Assuming that the *master* host has a working DNS configuration in place, the chroot environment can be updated with a copy of the configuration as follows:

```
[sms]# cp -p /etc/resolv.conf $CHROOT/etc/resolv.conf
```

Now, we can include additional components to the compute instance using `yum` to install into the chroot location defined previously:

```
# Add Slurm client support meta-package
[sms]# yum -y --installroot=$CHROOT install ohpc-slurm-client

# Add IB support and enable
[sms]# yum -y --installroot=$CHROOT groupinstall "InfiniBand Support"
[sms]# yum -y --installroot=$CHROOT install infinipath-psm
```

```
[sms]# chroot $CHROOT systemctl enable rdma

# Add Network Time Protocol (NTP) support
[sms]# yum -y --installroot=$CHROOT install ntp

# Add kernel drivers
[sms]# yum -y --installroot=$CHROOT install kernel

# Include modules user environment
[sms]# yum -y --installroot=$CHROOT install lmod-ohpc
```

### 4.7.3 Customize system configuration

Prior to assembling the image, it is advantageous to perform any additional customization within the chroot environment created for the desired *compute* instance. The following steps document the process to add a local *ssh* key created by Warewulf to support remote access, identify the resource manager server, configure NTP for compute resources, and enable NFS mounting of a `$HOME` file system and the public OpenHPC install path (`/opt/ohpc/pub`) that will be hosted by the *master* host in this example configuration.

```
# Initialize warewulf database and add new cluster key to base image
[sms]# wwinit database
[sms]# wwinit ssh_keys
[sms]# cat ~/.ssh/cluster.pub >> $CHROOT/root/.ssh/authorized_keys

# Add NFS client mounts of /home and /opt/ohpc/pub to base image
[sms]# echo "${sms_ip}:/home /home nfs nfsvers=3,rsz=1024,wsz=1024,cto 0 0" >> $CHROOT/etc/fstab
[sms]# echo "${sms_ip}:/opt/ohpc/pub /opt/ohpc/pub nfs nfsvers=3 0 0" >> $CHROOT/etc/fstab

# Export /home and OpenHPC public packages from master server
[sms]# echo "/home *(rw,no_subtree_check,fsid=10,no_root_squash)" >> /etc/exports
[sms]# echo "/opt/ohpc/pub *(ro,no_subtree_check,fsid=11)" >> /etc/exports
[sms]# exportfs -a
[sms]# systemctl restart nfs-server
[sms]# systemctl enable nfs-server

# Enable NTP time service on computes and identify master host as local NTP server
[sms]# chroot $CHROOT systemctl enable ntpd
[sms]# echo "server ${sms_ip}" >> $CHROOT/etc/ntp.conf
```

### 4.7.4 Additional Customization (*optional*)

This section highlights common additional customizations that can *optionally* be applied to the local cluster environment. These customizations include:

- Increase memlock limits
- Restrict ssh access to compute resources
- Add BeeGFS client
- Add Lustre client
- Enable syslog forwarding
- Add Nagios Core monitoring
- Add Ganglia monitoring
- Add ClusterShell
- Add *mrsh*
- Add *genders*
- Add ConMan

Details on the steps required for each of these customizations are discussed further in the following sections.

**4.7.4.1 Increase locked memory limits** In order to utilize InfiniBand as the underlying high speed interconnect, it is generally necessary to increase the locked memory settings for system users. This can be accomplished by updating the `/etc/security/limits.conf` file and this should be performed within the *compute* image and on all job submission hosts. In this recipe, jobs are submitted from the *master* host, and the following commands can be used to update the maximum locked memory settings on both the master host and the compute image:

```
# Update memlock settings on master
[sms]# perl -pi -e 's/# End of file/\* soft memlock unlimited\n$&/s' /etc/security/limits.conf
[sms]# perl -pi -e 's/# End of file/\* hard memlock unlimited\n$&/s' /etc/security/limits.conf

# Update memlock settings within compute image
[sms]# perl -pi -e 's/# End of file/\* soft memlock unlimited\n$&/s' $CHROOT/etc/security/limits.conf
[sms]# perl -pi -e 's/# End of file/\* hard memlock unlimited\n$&/s' $CHROOT/etc/security/limits.conf
```

**4.7.4.2 Enable ssh control via resource manager** An additional optional customization that is recommended is to restrict `ssh` access on compute nodes to only allow access by users who have an active job associated with the node. This can be enabled via the use of a pluggable authentication module (PAM) provided as part of the Slurm package installs. To enable this feature within the *compute* image, issue the following:

```
[sms]# echo "account required    pam_slurm.so" >> $CHROOT/etc/pam.d/sshd
```

**4.7.4.3 Add Lustre client** To add Lustre client support on the cluster, it necessary to install the client and associated modules on each host needing to access a Lustre file system. In this recipe, it is assumed that the Lustre file system is hosted by servers that are pre-existing and are not part of the install process. Outlining the variety of Lustre client mounting options is beyond the scope of this document, but the general requirement is to add a mount entry for the desired file system that defines the management server (MGS) and underlying network transport protocol. To add client mounts on both the *master* server and *compute* image, the following commands can be used. Note that the Lustre file system to be mounted is identified by the  `${mgs_fs_name}`  variable. In this example, the file system is configured to be mounted locally as `/mnt/lustre`.

```
# Add Lustre client software to master host
[sms]# yum -y install lustre-client-ohpc lustre-client-ohpc-modules
```

```
# Include Lustre client software in compute image
[sms]# yum -y --installroot=$CHROOT install lustre-client-ohpc lustre-client-ohpc-modules

# Include mount point and file system mount in compute image
[sms]# mkdir $CHROOT/mnt/lustre
[sms]# echo "${mgs_fs_name} /mnt/lustre lustre defaults,_netdev,localflock 0 0" >> $CHROOT/etc/fstab
```

The default underlying network type used by Lustre is *tcp*. If your external Lustre file system is to be mounted using a network type other than *tcp*, additional configuration files are necessary to identify the desired network type. The example below illustrates creation of modprobe configuration files instructing Lustre to use an InfiniBand network with the **o2ib** LNET driver attached to `ib0`. Note that these modifications are made to both the *master* host and *compute* image.

```
[sms]# echo "options lnet networks=o2ib(ib0)" >> /etc/modprobe.d/lustre.conf  
[sms]# echo "options lnet networks=o2ib(ib0)" >> $CHROOT/etc/modprobe.d/lustre.conf
```

With the Lustre configuration complete, the client can be mounted on the *master* host as follows:

```
[sms]# mkdir /mnt/lustre  
[sms]# mount -t lustre -o localflock ${mgs_fs_name} /mnt/lustre
```

**4.7.4.4 Enable forwarding of system logs** It is often desirable to consolidate system logging information for the cluster in a central location, both to provide easy access to the data, and to reduce the impact of storing data inside the stateless compute node's memory footprint. The following commands highlight the steps necessary to configure compute nodes to forward their logs to the SMS, and to allow the SMS to accept these log requests.

```
# Configure SMS to receive messages and reload rsyslog configuration
[sms]# perl -pi -e "s/\\#\\$ModLoad imudp/\\$ModLoad imudp/" /etc/rsyslog.conf
[sms]# perl -pi -e "s/\\#\\$UDPServerRun 514/\\$UDPServerRun 514/" /etc/rsyslog.conf
[sms]# systemctl restart rsyslog

# Define compute node forwarding destination
[sms]# echo ".* @$${sms_ip}:514" >> $CHROOT/etc/rsyslog.conf

# Disable most local logging on computes. Emergency and boot logs will remain on the compute nodes
[sms]# perl -pi -e "s/^*.info/\\#*.info/" $CHROOT/etc/rsyslog.conf
[sms]# perl -pi -e "s/^authpriv/\\#authpriv/" $CHROOT/etc/rsyslog.conf
[sms]# perl -pi -e "s/^mail/\\#mail/" $CHROOT/etc/rsyslog.conf
[sms]# perl -pi -e "s/^cron/\\#cron/" $CHROOT/etc/rsyslog.conf
[sms]# perl -pi -e "s/^uucp/\\#uucp/" $CHROOT/etc/rsyslog.conf
```

**4.7.4.5 Add Nagios monitoring** Nagios is an open source infrastructure monitoring package that monitors servers, switches, applications, and services and offers user-defined alerting facilities. As provided by OpenHPC, it consists of a base monitoring daemon and a set of plug-ins for monitoring various aspects of an HPC cluster. The following commands can be used to install and configure a Nagios server on the *master* node, and add the facility to run tests and gather metrics from provisioned *compute* nodes.

```
# Install Nagios meta-package on master host
[sms]# yum -y install ohpc-nagios

# Install plugins into compute node image
[sms]# yum -y --installroot=$CHROOT install nagios-plugins-all-ohpc nrpe-ohpc

# Enable and configure NRPE in compute image
[sms]# chroot $CHROOT systemctl enable nrpe
[sms]# perl -pi -e "s/^allowed_hosts=/# allowed_hosts=/" $CHROOT/etc/nagios/nrpe.cfg
[sms]# echo "nrpe 5666/tcp # NRPE" >> $CHROOT/etc/services
[sms]# echo "nrpe : ${sms_ip} : ALLOW" >> $CHROOT/etc/hosts.allow
[sms]# echo "nrpe : ALL : DENY" >> $CHROOT/etc/hosts.allow
[sms]# chroot $CHROOT /usr/sbin/useradd -c "NRPE user for the NRPE service" -d /var/run/nrpe \
    -r -g nrpe -s /sbin/nologin nrpe
[sms]# chroot $CHROOT /usr/sbin/groupadd -r nrpe

# Configure remote services to test on compute nodes
[sms]# mv /etc/nagios/conf.d/services.cfg.example /etc/nagios/conf.d/services.cfg

# Define compute nodes as hosts to monitor
[sms]# mv /etc/nagios/conf.d/hosts.cfg.example /etc/nagios/conf.d/hosts.cfg
[sms]# for ((i=0; i<num_computes; i++)); do
    perl -pi -e "s/HOSTNAME$((i+1))/${c_name[$i]}/ || s/HOST$((i+1))_IP/${c_ip[$i]}/" \
        /etc/nagios/conf.d/hosts.cfg
done

# Update location of mail binary for alert commands
[sms]# perl -pi -e "s/ \\bin\\mail/ \\usr\\bin\\mailx/g" /etc/nagios/objects/commands.cfg

# Update email address of contact for alerts
[sms]# perl -pi -e "s/nagios@localhost/root@${sms_name}/" /etc/nagios/objects/contacts.cfg
```

```
# Add check_ssh command for remote hosts
[sms]# echo command[check_ssh]=/usr/lib64/nagios/plugins/check_ssh localhost \
    >> $CHROOT/etc/nagios/nrpe.cfg

# Enable Nagios on master, and configure
[sms]# chkconfig nagios on
[sms]# systemctl start nagios
[sms]# chmod u+s `which ping`
```

**4.7.4.6 Add Ganglia monitoring** Ganglia is a scalable distributed system monitoring tool for high-performance computing systems such as clusters and grids. It allows the user to remotely view live or historical statistics (such as CPU load averages or network utilization) for all machines running the *gmond* daemon. The following commands can be used to enable Ganglia to monitor both the *master* and *compute* hosts.

```
# Install Ganglia meta-package on master
[sms]# yum -y install ohpc-ganglia

# Install Ganglia compute node daemon
[sms]# yum -y --installroot=$CHROOT install ganglia-gmond-ohpc

# Use example configuration script to enable unicast receiver on master host
[sms]# cp /opt/ohpc/pub/examples/ganglia/gmond.conf /etc/ganglia/gmond.conf
[sms]# perl -pi -e "s/<sms>/{sms_name}/" /etc/ganglia/gmond.conf

# Add configuration to compute image and provide gridname
[sms]# cp /etc/ganglia/gmond.conf $CHROOT/etc/ganglia/gmond.conf
[sms]# echo "gridname MySite" >> /etc/ganglia/gmetad.conf

# Start and enable Ganglia services
[sms]# systemctl enable gmond
[sms]# systemctl enable gmetad
[sms]# systemctl start gmond
[sms]# systemctl start gmetad
[sms]# chroot $CHROOT systemctl enable gmond

# Restart web server
[sms]# systemctl try-restart httpd
```

Once enabled and running, Ganglia should provide access to a web-based monitoring console on the *master* host. Read access to monitoring metrics will be enabled by default and can be accessed via a web browser. When running a web browser directly on the *master* host, the Ganglia top-level overview is available at <http://localhost/ganglia>. When accessing remotely, replace *localhost* with the chosen name of your master host (`{sms_name}`).

**4.7.4.7 Add ClusterShell** ClusterShell is an event-based Python library to execute commands in parallel across cluster nodes. Installation and basic configuration defining three node groups (*adm*, *compute*, and *all*) is as follows:

```
# Install ClusterShell
[sms]# yum -y install clustershell-ohpc

# Setup node definitions
[sms]# cd /etc/clustershell/groups.d
[sms]# mv local.cfg local.cfg.orig
[sms]# echo "adm: {sms_name}" > local.cfg
[sms]# echo "compute: ${compute_prefix}[1-#{num_computes}]" >> local.cfg
[sms]# echo "all: @adm,@compute" >> local.cfg
```

**4.7.4.8 Add *mrsh*** *mrsh* is a secure remote shell utility, like *ssh*, which uses *munge* for authentication and encryption. By using the *munge* installation used by Slurm, *mrsh* provides shell access to systems using the same *munge* key without having to track *ssh* keys. Like *ssh*, *mrsh* provides a remote copy command, *mrcp*, and can be used as a *rcmd* by *pdsh*. Example installation and configuration is as follows:

```
# Install mrsh
[sms]# yum -y install mrsh-ohpc mrsh-rsh-compat-ohpc
[sms]# yum -y --installroot=$CHROOT install mrsh-ohpc mrsh-rsh-compat-ohpc mrsh-server-ohpc

# Identify mshell and mlogin in services file
[sms]# echo "mshell      21212/tcp      # mrshd" >> /etc/services
[sms]# echo "mlogin      541/tcp      # mrlogind" >> /etc/services

# Enable xinetd in compute node image
[sms]# chroot $CHROOT systemctl enable xinetd
```

**4.7.4.9 Add *genders*** *genders* is a static cluster configuration database or node typing database used for cluster configuration management. Other tools and users can access the *genders* database in order to make decisions about where an action, or even what action, is appropriate based on associated types or "genders". Values may also be assigned to and retrieved from a *gender* to provide further granularity. The following example highlights installation and configuration of two genders: *compute* and *bmc*.

```
# Install genders
[sms]# yum -y install genders-ohpc

# Generate a sample genders file
[sms]# echo -e "${sms_name}\tsms" > /etc/genders
[sms]# for ((i=0; i<$num_computes; i++)) ; do
    echo -e "${c_name[$i]}\tcompute,bmc=${c_bmc[$i]}"
done >> /etc/genders
```

**4.7.4.10 Add ConMan** ConMan is a serial console management program designed to support a large number of console devices and simultaneous users. It supports logging console device output and connecting to compute node consoles via IPMI serial-over-lan. Installation and example configuration is outlined below.

```
# Install conman to provide a front-end to compute consoles and log output
[sms]# yum -y install conman-ohpc

# Configure conman for computes (note your IPMI password is required for console access)
[sms]# for ((i=0; i<$num_computes; i++)) ; do
    echo -n 'CONSOLE name='${c_name[$i]}' dev="ipmi:${c_bmc[$i]}" '
    echo 'ipmiopts="U:${bmc_username},P:${IPMI_PASSWORD:-undefined},W:solpayloadsize"'
done >> /etc/conman.conf

# Enable and start conman
[sms]# systemctl enable conman
[sms]# systemctl start conman
```

Note that an additional kernel boot option is typically necessary to enable serial console output. This option is highlighted in §4.8.4 after compute nodes have been registered with the provisioning system.

### 4.7.5 Import files

The Warewulf system includes functionality to import arbitrary files from the provisioning server for distribution to managed hosts. This is one way to distribute user credentials to *compute* nodes. To import local file-based credentials, issue the following:

```
[sms]# wwsh file import /etc/passwd
[sms]# wwsh file import /etc/group
[sms]# wwsh file import /etc/shadow
```

Similarly, to import the global Slurm configuration file and the cryptographic key that is required by the *munge* authentication library to be available on every host in the resource management pool, issue the following:

```
[sms]# wwsh file import /etc/slurm/slurm.conf
[sms]# wwsh file import /etc/munge/munge.key
```

Finally, to add *optional* support for controlling IPoIB interfaces (see §4.5), OpenHPC includes a template file for Warewulf that can optionally be imported and used later to provision *ib0* network settings.

```
[sms]# wwsh file import /opt/ohpc/pub/examples/network/centos/ifcfg-ib0.ww
[sms]# wwsh -y file set ifcfg-ib0.ww --path=/etc/sysconfig/network-scripts/ifcfg-ib0
```

## 4.8 Finalizing provisioning configuration

Warewulf employs a two-stage boot process for provisioning nodes via creation of a bootstrap image that is used to initialize the process, and a virtual node file system capsule containing the full system image. This section highlights creation of the necessary provisioning images, followed by the registration of desired compute nodes.

### 4.8.1 Assemble bootstrap image

The bootstrap image includes the runtime kernel and associated modules, as well as some simple scripts to complete the provisioning process. The following commands highlight the inclusion of additional drivers and creation of the bootstrap image based on the running kernel.

```
# (Optional) Include BeeGFS/Lustre drivers; needed if enabling additional kernel modules on computes
[sms]# export WW_CONF=/etc/warewulf/bootstrap.conf
[sms]# echo "drivers += updates/kernel/" >> $WW_CONF

# (Optional) Include overlayfs drivers; needed by Singularity
[sms]# echo "drivers += overlay" >> $WW_CONF

# Build bootstrap image
[sms]# wwbootstrap `uname -r`
```

### 4.8.2 Assemble Virtual Node File System (VNFS) image

With the local site customizations in place, the following step uses the `wwvnfs` command to assemble a VNFS capsule from the chroot environment defined for the *compute* instance.

```
[sms]# wwvnfs --chroot $CHROOT
```

### 4.8.3 Register nodes for provisioning

In preparation for provisioning, we can now define the desired network settings for four example compute nodes with the underlying provisioning system and restart the `dhcp` service. Note the use of variable names for the desired compute hostnames, node IPs, and MAC addresses which should be modified to accommodate local settings and hardware. By default, Warewulf uses network interface names of the `eth#` variety and adds kernel boot arguments to maintain this scheme on newer kernels. Consequently, when specifying the desired provisioning interface via the `$eth_provision` variable, it should follow this convention. Alternatively, if you prefer to use the predictable network interface naming scheme (e.g. names like `en4s0f0`), additional steps are included to alter the default kernel boot arguments and take the `eth#` named interface down after bootstrapping so the normal init process can bring it up again using the desired name.

Also included in these steps are commands to enable Warewulf to manage IPoIB settings and corresponding definitions of IPoIB addresses for the compute nodes. This is typically optional unless you are planning to include a Lustre client mount over InfiniBand. The final step in this process associates the VNFS image assembled in previous steps with the newly defined compute nodes, utilizing the user credential files and munge key that were imported in §4.7.5.

```
# Set provisioning interface as the default networking device
[sms]# echo "GATEWAYDEV=${eth_provision}" > /tmp/network.$$
[sms]# wwsh -y file import /tmp/network.$$ --name network
[sms]# wwsh -y file set network --path /etc/sysconfig/network --mode=0644 --uid=0

# Add nodes to Warewulf data store
[sms]# for ((i=0; i<$num_computes; i++)); do
    wwsh -y node new ${c_name[i]} --ipaddr=${c_ip[i]} --hwaddr=${c_mac[i]} -D ${eth_provision}
done
```

```
# Additional step required if desiring to use predictable network interface
# naming schemes (e.g. en4s0f0). Skip if using eth# style names.
[sms]# wwsh provision set "${compute_regex}" --kargs "net.ifnames=1,biosdevname=1"
[sms]# wwsh provision set --postnetdown=1 "${compute_regex}"
```

```
# Define provisioning image for hosts
[sms]# wwsh -y provision set "${compute_regex}" --vnfs=centos7.3 --bootstrap='uname -r' \
    --files=dynamic_hosts,password,group,shadow,slurm.conf,munge.key,network
```

```
# Optionally define IPoIB network settings (required if planning to mount Lustre over IB)
[sms]# for ((i=0; i<$num_computes; i++)); do
    wwsh -y node set ${c_name[i]} -D ib0 --ipaddr=${c_ipoib[i]} --netmask=${ipoib_netmask}
done
[sms]# wwsh -y provision set "${compute_regex}" --fileadd=ifcfg-ib0.ww
```

### Tip

Warewulf includes a utility named `wnodescan` to automatically register new compute nodes versus the outlined node-addition approach which requires hardware MAC addresses to be gathered in advance. With `wnodescan`, nodes will be added to the Warewulf database in the order in which their DHCP requests are received by the master, so care must be taken to boot nodes in the order one wishes to see preserved in the Warewulf database. The IP address provided will be incremented after each node is found, and the utility will exit after all specified nodes have been found. Example usage is highlighted below:

```
[sms]# wnodescan --netdev=${eth_provision} --ipaddr=${c_ip[0]} --netmask=${internal_netmask} \
    --vnfs=centos7.3 --bootstrap='uname -r' --listen=${sms_eth_internal} ${c_name[0]}-${c_name[3]}
```

```
# Restart dhcp / update PXE
[sms]# systemctl restart dhcpd
[sms]# wwsh pxe update
```

## 4.8.4 Optional kernel arguments

If you chose to enable ConMan in §4.7.4.10, additional boot-time kernel arguments are needed to enable serial console redirection. An example provisioning setting which adds to any other kernel arguments defined in `${kargs}` is as follows:

```
# Define node kernel arguments to support SOL console
[sms]# wvsh -y provision set "${compute_regex}" --kargs "${kargs} console=ttyS1,115200"
```

#### 4.8.5 Optionally configure stateful provisioning

Warewulf normally defaults to running the assembled VNFS image out of system memory in a *stateless* configuration. Alternatively, Warewulf can also be used to partition and format persistent storage such that the VNFS image can be installed locally to disk in a *stateful* manner. This does, however, require that a boot loader (GRUB) be added to the image as follows:

```
# Add GRUB2 bootloader and re-assemble VNFS image
[sms]# yum -y --installroot=$CHROOT install grub2
[sms]# wvvnfs --chroot $CHROOT
```

Enabling stateful nodes also requires additional site-specific, disk-related parameters in the Warewulf configuration. In the example that follows, the compute node configuration is updated to define where to install the GRUB bootloader, which disk to partition, which partition to format, and what the filesystem layout will look like.

```
# Update node object parameters
[sms]# export sda1="mountpoint=/boot:dev=sda1:type=ext3:size=500"
[sms]# export sda2="dev=sda2:type=swap:size=32768"
[sms]# export sda3="mountpoint=/:dev=sda3:type=ext3:size=fill"
[sms]# wvsh -y object modify -s bootloader=sda -t node "${compute_regex}"
[sms]# wvsh -y object modify -s diskpartition=sda -t node "${compute_regex}"
[sms]# wvsh -y object modify -s diskformat=sda1,sda2,sda3 -t node "${compute_regex}"
[sms]# wvsh -y object modify -s filesystems="$sda1,$sda2,$sda3" -t node "${compute_regex}"
```

Upon subsequent reboot of the modified nodes, Warewulf will partition and format the disk to host the desired VNFS image. Once installed to disk, Warewulf can be instructed to subsequently boot from local storage (alternatively, the BIOS boot option order could be updated to reflect a desire to boot from disk):

```
# After provisioning, update node object parameters to boot from local storage
[sms]# wvsh -y object modify -s bootlocal=EXIT -t node "${compute_regex}"
```

Deleting the bootlocal object parameter will cause Warewulf to once again reformat and re-install to local storage upon a new PXE boot request.

### 4.9 Boot compute nodes

At this point, the *master* server should be able to boot the newly defined compute nodes. Assuming that the compute node BIOS settings are configured to boot over PXE, all that is required to initiate the provisioning process is to power cycle each of the desired hosts using IPMI access. The following commands use the `ipmitool` utility to initiate power resets on each of the four compute hosts. Note that the utility requires that the `IPMI_PASSWORD` environment variable be set with the local BMC password in order to work interactively.

```
[sms]# for ((i=0; i<${num_computes}; i++)) ; do
    ipmitool -E -I lanplus -H ${c_bmc[$i]} -U ${bmc_username} chassis power reset
done
```

Once kicked off, the boot process should take less than 5 minutes (depending on BIOS post times) and you can verify that the compute hosts are available via ssh, or via parallel ssh tools to multiple hosts. For

example, to run a command on the newly imaged compute hosts using `pdsh`, execute the following:

```
[sms]# pdsh -w c[1-4] uptime
c1 05:03am up 0:02, 0 users, load average: 0.20, 0.13, 0.05
c2 05:03am up 0:02, 0 users, load average: 0.20, 0.14, 0.06
c3 05:03am up 0:02, 0 users, load average: 0.19, 0.15, 0.06
c4 05:03am up 0:02, 0 users, load average: 0.15, 0.12, 0.05
```

### Tip

While the `pxelinux.0` and `lpxelinux.0` files that ship with Warewulf to enable network boot support a wide range of hardware, some hosts may boot more reliably or faster using the BOS versions provided via the `syslinux-tftpboot` package. If you encounter PXE issues, consider replacing the `pxelinux.0` and `lpxelinux.0` files supplied with `warewulf-provision-ohpc` with versions from `syslinux-tftpboot`.

## 5 Install OpenHPC Development Components

The install procedure outlined in §4 highlighted the steps necessary to install a *master* host, assemble and customize a *compute* image, and provision several compute hosts from bare-metal. With these steps completed, additional OpenHPC-provided packages can now be added to support a flexible HPC development environment including development tools, C/C++/Fortran compilers, MPI stacks, and a variety of 3rd party libraries. The following subsections highlight the additional software installation procedures.

### 5.1 Development Tools

To aid in general development efforts, OpenHPC provides recent versions of the GNU autotools collection, the Valgrind memory debugger, EasyBuild, and Spack. These can be installed as follows:

```
# Install autotools meta-package
[sms]# yum -y install ohpc-autotools

[sms]# yum -y install EasyBuild-ohpc
[sms]# yum -y install hwloc-ohpc
[sms]# yum -y install spack-ohpc
[sms]# yum -y install valgrind-ohpc
```

### 5.2 Compilers

OpenHPC presently packages the GNU compiler toolchain integrated with the underlying modules-environment system in a hierarchical fashion. The modules system will conditionally present compiler-dependent software based on the toolchain currently loaded.

```
[sms]# yum -y install gnu7-compilers-ohpc
```

The llvm compiler toolchains are also provided as a standalone additional compiler family (ie. users can easily switch between gcc/clang environments), but we do not provide the full complement of downstream library builds.

```
[sms]# yum -y install llvm4-compilers-ohpc
```

### 5.3 MPI Stacks

For MPI development support, OpenHPC presently provides pre-packaged builds for two MPI families. Note that for this **Tech Preview** release, MPI tests have only been carried using an *ethernet* transport layer.

```
[sms]# yum -y install openmpi-gnu7-ohpc mpich-gnu7-ohpc
```

### 5.4 Performance Tools

OpenHPC provides a variety of open-source tools to aid in application performance analysis (refer to Appendix E for a listing of available packages). This group of tools can be installed as follows:

```
# Install perf-tools meta-package
[sms]# yum -y install ohpc-gnu7-perf-tools
```

### 5.5 Setup default development environment

System users often find it convenient to have a default development environment in place so that compilation can be performed directly for parallel programs requiring MPI. This setup can be conveniently enabled via modules and the OpenHPC modules environment is pre-configured to load an `ohpc` module on login (if present). The following package install provides a default environment that enables autotools, the GNU compiler toolchain, and the MVAPICH2 MPI stack.

```
[sms]# yum -y install lmod-defaults-gnu7-mvapich2-ohpc
```

#### Tip

If you want to change the default environment from the suggestion above, OpenHPC also provides the GNU compiler toolchain with the OpenMPI and MPICH stacks:

- `lmod-defaults-gnu7-openmpi-ohpc`
- `lmod-defaults-gnu7-mpich-ohpc`

### 5.6 3rd Party Libraries and Tools

OpenHPC provides pre-packaged builds for a number of popular open-source tools and libraries used by HPC applications and developers. For example, OpenHPC provides builds for FFTW and HDF5 (including serial and parallel I/O support), and the GNU Scientific Library (GSL). Again, multiple builds of each package are available in the OpenHPC repository to support multiple compiler and MPI family combinations where appropriate. Note, however, that not all combinatorial permutations may be available for components where there are known license incompatibilities. The general naming convention for builds provided by OpenHPC is to append the compiler and MPI family name that the library was built against directly into the package name. For example, libraries that do not require MPI as part of the build process adopt the following RPM name:

```
package-<compiler_family>-ohpc-<package_version>-<release>.rpm
```

Packages that do require MPI as part of the build expand upon this convention to additionally include the MPI family name as follows:

```
package-<compiler_family>-<mpi_family>-ohpc-<package_version>-<release>.rpm
```

To illustrate this further, the command below queries the locally configured repositories to identify all of the available PETSc packages that were built with the GNU toolchain. The resulting output that is included shows that pre-built versions are available for each of the supported MPI families presented in §5.3.

```
[sms]# yum search petsc-gnu7 ohpc
Loaded plugins: fastestmirror
Loading mirror speeds from cached hostfile
===== N/S matched: petsc-gnu7, ohpc =====
petsc-gnu7-impi-ohpc.x86_64 : Portable Extensible Toolkit for Scientific Computation
petsc-gnu7-mpich-ohpc.x86_64 : Portable Extensible Toolkit for Scientific Computation
petsc-gnu7-mvapich2-ohpc.x86_64 : Portable Extensible Toolkit for Scientific Computation
petsc-gnu7-openmpi-ohpc.x86_64 : Portable Extensible Toolkit for Scientific Computation
```

### Tip

OpenHPC-provided 3rd party builds are configured to be installed into a common top-level repository so that they can be easily exported to desired hosts within the cluster. This common top-level path (`/opt/ohpc/pub`) was previously configured to be mounted on *compute* nodes in §4.7.3, so the packages will be immediately available for use on the cluster after installation on the *master* host.

For convenience, OpenHPC provides package aliases for these 3rd party libraries and utilities that can be used to install available libraries for use with the GNU compiler family toolchain. For parallel libraries, aliases are grouped by MPI family toolchain so that administrators can choose a subset should they favor a particular MPI stack. Please refer to Appendix E for a more detailed listing of all available packages in each of these functional areas. To install all available package offerings within OpenHPC, issue the following:

```
# Install 3rd party libraries/tools meta-packages built with GNU toolchain
[sms]# yum -y install ohpc-gnu7-serial-libs
[sms]# yum -y install ohpc-gnu7-io-libs
[sms]# yum -y install ohpc-gnu7-python-libs
[sms]# yum -y install ohpc-gnu7-runtimes
```

```
# Install parallel lib meta-packages for all available MPI toolchains
[sms]# yum -y install ohpc-gnu7-mpich-parallel-libs
[sms]# yum -y install ohpc-gnu7-openmpi-parallel-libs
```

## 6 Resource Manager Startup

In section §4, the Slurm resource manager was installed and configured for use on both the *master* host and *compute* node instances. With the cluster nodes up and functional, we can now startup the resource manager services in preparation for running user jobs. Generally, this is a two-step process that requires starting up the controller daemons on the *master* host and the client daemons on each of the *compute* hosts. Note that Slurm leverages the use of the *munge* library to provide authentication services and this daemon also needs to be running on all hosts within the resource management pool. The following commands can be used to startup the necessary services to support resource management under Slurm.

```
# Start munge and slurm controller on master host
[sms]# systemctl enable munge
[sms]# systemctl enable slurmctld
[sms]# systemctl start munge
[sms]# systemctl start slurmctld

# Start slurm clients on compute hosts
[sms]# pdsh -w $compute_prefix[1-4] systemctl start slurmd
```

## 7 Run a Test Job

With the resource manager enabled for production usage, users should now be able to run jobs. To demonstrate this, we will add a “test” user on the *master* host that can be used to run an example job.

```
[sms]# useradd -m test
```

Warewulf installs a utility on the compute nodes to automatically synchronize known files from the provisioning server at five minute intervals. In this recipe, recall that we previously registered credential files with Warewulf (e.g. `passwd`, `group`, and `shadow`) so that these files would be propagated during compute node imaging. However, with the addition of a new “test” user above, the files have been outdated and we need to update the Warewulf database to incorporate the additions. This re-sync process can be accomplished as follows:

```
[sms]# wwsh file resync passwd shadow group
```

### Tip

After re-syncing to notify Warewulf of file modifications made on the *master* host, it should take approximately 5 minutes for the changes to propagate. However, you can also manually pull the changes from compute nodes via the following:

```
[sms]# pdsh -w $compute_prefix[1-4] /warewulf/bin/wwgetfiles
```

OpenHPC includes a simple “hello-world” MPI application in the `/opt/ohpc/pub/examples` directory that can be used for this quick compilation and execution. OpenHPC also provides a companion job-launch script named `prun` that is installed in concert with the pre-packaged MPI toolchains. At present, OpenHPC is unable to include the PMI process management server normally included within Slurm which implies that `srund` cannot be used for MPI job launch. Instead, native job launch mechanisms provided by the MPI stacks are utilized and `prun` abstracts this process for the various stacks to retain a single launch command.

### 7.1 Interactive execution

To use the newly created “test” account to compile and execute the application *interactively* through the resource manager, execute the following (note the use of `prun` for parallel job launch which summarizes the underlying native job launch mechanism being used):

```
# Switch to "test" user
```

```
[sms]# su - test

# Compile MPI "hello world" example
[test@sms ~]$ mpicc -O3 /opt/ohpc/pub/examples/mpi/hello.c

# Submit interactive job request and use prun to launch executable
[test@sms ~]$ srun -n 8 -N 2 --pty /bin/bash

[test@c1 ~]$ prun ./a.out

[prun] Master compute host = c1
[prun] Resource manager = slurm
[prun] Launch cmd = mpiexec.hydra -bootstrap slurm ./a.out

Hello, world (8 procs total)
--> Process # 0 of 8 is alive. -> c1
--> Process # 4 of 8 is alive. -> c2
--> Process # 1 of 8 is alive. -> c1
--> Process # 5 of 8 is alive. -> c2
--> Process # 2 of 8 is alive. -> c1
--> Process # 6 of 8 is alive. -> c2
--> Process # 3 of 8 is alive. -> c1
--> Process # 7 of 8 is alive. -> c2
```

### Tip

The following table provides approximate command equivalences between SLURM and PBS Pro:

| Command                          | PBS Pro              | SLURM                        |
|----------------------------------|----------------------|------------------------------|
| Submit <i>batch</i> job          | qsub [job script]    | sbatch [job script]          |
| Request <i>interactive</i> shell | qsub -I /bin/bash    | srun -pty /bin/bash          |
| Delete job                       | qdel [job id]        | scancel [job id]             |
| Queue status                     | qstat -q             | sinfo                        |
| Job status                       | qstat -f [job id]    | scontrol show job [job id]   |
| Node status                      | pbsnodes [node name] | scontrol show node [node id] |

## 7.2 Batch execution

For batch execution, OpenHPC provides a simple job script for reference (also housed in the `/opt/ohpc/pub/examples` directory). This example script can be used as a starting point for submitting batch jobs to the resource manager and the example below illustrates use of the script to submit a batch job for execution using the same executable referenced in the previous interactive example.

```
# Copy example job script
[test@sms ~]$ cp /opt/ohpc/pub/examples/slurm/job.mpi .

# Examine contents (and edit to set desired job sizing characteristics)
[test@sms ~]$ cat job.mpi
#!/bin/bash

#SBATCH -J test           # Job name
#SBATCH -o job.%j.out     # Name of stdout output file (%j expands to %jobId)
#SBATCH -N 2              # Total number of nodes requested
#SBATCH -n 16             # Total number of mpi tasks #requested
#SBATCH -t 01:30:00       # Run time (hh:mm:ss) - 1.5 hours

# Launch MPI-based executable

prun ./a.out

# Submit job for batch execution
[test@sms ~]$ sbatch job.mpi
Submitted batch job 339
```

### Tip

The use of the `%j` option in the example batch job script shown is a convenient way to track application output on an individual job basis. The `%j` token is replaced with the Slurm job allocation number once assigned (job #339 in this example).

## Appendices

### A Installation Template

This appendix highlights the availability of a companion installation script that is included with OpenHPC documentation. This script, when combined with local site inputs, can be used to implement a starting recipe for bare-metal system installation and configuration. This template script is used during validation efforts to test cluster installations and is provided as a convenience for administrators as a starting point for potential site customization.

#### Tip

Note that the template script provided is intended for use during initial installation and is not designed for repeated execution. If modifications are required after using the script initially, we recommend running the relevant subset of commands interactively.

The template script relies on the use of a simple text file to define local site variables that were outlined in §2.3. By default, the template installation script attempts to use local variable settings sourced from the `/opt/ohpc/pub/doc/recipes/vanilla/input.local` file, however, this choice can be overridden by the use of the `${OHPC_INPUT_LOCAL}` environment variable. The template install script is intended for execution on the SMS *master* host and is installed as part of the `docs-ohpc` package into `/opt/ohpc/pub/doc/recipes/vanilla/recipe.sh`. After enabling the OpenHPC repository and reviewing the guide for additional information on the intent of the commands, the general starting approach for using this template is as follows:

1. Install the `docs-ohpc` package

```
[sms]# yum -y install docs-ohpc
```

2. Copy the provided template input file to use as a starting point to define local site settings:

```
[sms]# cp /opt/ohpc/pub/doc/recipes/centos7/input.local input.local
```

3. Update `input.local` with desired settings
4. Copy the template installation script which contains command-line instructions culled from this guide.

```
[sms]# cp -p /opt/ohpc/pub/doc/recipes/centos7/aarch64/warewulf/slurm/recipe.sh .
```

5. Review and edit `recipe.sh` to suite.
6. Use environment variable to define local input file and execute `recipe.sh` to perform a local installation.

```
[sms]# export OHPC_INPUT_LOCAL=./input.local
[sms]# ./recipe.sh
```

## B Upgrading OpenHPC Packages

As newer OpenHPC releases are made available, users are encouraged to upgrade their locally installed packages against the latest repository versions to obtain access to bug fixes and newer component versions. This can be accomplished with the underlying package manager as OpenHPC packaging maintains versioning state across releases. Also, package builds available from the OpenHPC repositories have “-ohpc” appended to their names so that wild cards can be used as a simple way to obtain updates. The following general procedure highlights a method for upgrading existing installations. When upgrading from a minor release older than v1.3, you will first need to update your local OpenHPC repository configuration to point against the v1.3 release (or update your locally hosted mirror). Refer to §4.1 for more details on enabling the latest repository. In contrast, when upgrading between micro releases on the same branch (e.g. from v1.3 to 1.3.2), there is no need to adjust local package manager configurations when using the public repository as rolling updates are pre-configured.

1. (Optional) Ensure repo metadata is current (on head node and in chroot location(s)). Package managers will naturally do this on their own over time, but if you are wanting to access updates immediately after a new release, the following can be used to sync to the latest.

```
[sms]# yum clean expire-cache  
[sms]# yum --installroot=$CHROOT clean expire-cache
```

2. Upgrade master (SMS) node

```
[sms]# yum -y upgrade "*-ohpc"
```

3. Upgrade packages in compute image

```
[sms]# yum -y --installroot=$CHROOT upgrade "*-ohpc"
```

4. Rebuild image(s)

```
[sms]# wwnfs --chroot $CHROOT
```

In the case where packages were upgraded within the chroot compute image, you will need to reboot the compute nodes when convenient to enable the changes.

### B.1 New component variants

As newer variants of key compiler/MPI stacks are released, OpenHPC will periodically add toolchains enabling the latest variant. To stay consistent throughout the build hierarchy, minimize recompilation requirements for existing binaries, and allow for multiple variants to coexist, unique delimiters are used to distinguish RPM package names and module hierarchy.

In the case of a fresh install, OpenHPC recipes default to installation of the latest toolchains available in a given release branch. However, if upgrading a previously installed system, administrators can *opt-in* to enable new variants as they become available. To illustrate this point, consider the previous OpenHPC 1.3.1 release as an example which introduced a new “gnu7” compiler variant providing GCC 7.x along with runtimes and libraries compiled with the newer toolchain. Note that prior to the 1.3.1 release, the “gnu” variant was available which provided GCC 5.x versions. In the case where an admin would like to enable the newer gnu7 toolchain, installation of these additions is simplified with the use of OpenHPC’s meta-packages (see Table 1 in Appendix E). The following example illustrates adding the complete “gnu7” toolchain environment leveraging convenience meta-packages and also updates the modules environment to make it the default.

```
# Update default environment
[sms]# yum -y remove lmod-defaults-gnu-mvapich2-ohpc
[sms]# yum -y install lmod-defaults-gnu7-mvapich2-ohpc

# Install GCC 7.x-compiled meta-packages with dependencies
[sms]# yum -y install ohpc-gnu7-perf-tools \
                    ohpc-gnu7-serial-libs \
                    ohpc-gnu7-io-libs \
                    ohpc-gnu7-python-libs \
                    ohpc-gnu7-runtimes \
                    ohpc-gnu7-mpich-parallel-libs \
                    ohpc-gnu7-openmpi-parallel-libs \
                    ohpc-gnu7-mvapich2-parallel-libs
```

## C Integration Test Suite

This appendix details the installation and basic use of the integration test suite used to support OpenHPC releases. This suite is not intended to replace the validation performed by component development teams, but is instead, devised to confirm component builds are functional and interoperable within the modular OpenHPC environment. The test suite is generally organized by components and the OpenHPC CI workflow relies on running the full suite using [Jenkins](#) to test multiple OS configurations and installation recipes. To facilitate customization and running of the test suite locally, we provide these tests in a standalone RPM.

```
[sms]# yum -y install test-suite-ohpc
```

The RPM installation creates a user named `ohpc-test` to house the test suite and provide an isolated environment for execution. Configuration of the test suite is done using standard GNU autotools semantics and the [BATS](#) shell-testing framework is used to execute and log a number of individual unit tests. Some tests require privileged execution, so a different combination of tests will be enabled depending on which user executes the top-level `configure` script. Non-privileged tests requiring execution on one or more compute nodes are submitted as jobs through the SLURM resource manager. The tests are further divided into “short” and “long” run categories. The short run configuration is a subset of approximately 180 tests to demonstrate basic functionality of key components (e.g. MPI stacks) and should complete in 10-20 minutes. The long run (around 1000 tests) is comprehensive and can take an hour or more to complete.

Most components can be tested individually, but a default configuration is setup to enable collective testing. To test an isolated component, use the `configure` option to disable all tests, then re-enable the desired test to run. The `--help` option to `configure` will display all possible tests. Example output is shown below (some output is omitted for the sake of brevity).

```
[sms]# su - ohpc-test
[test@sms ~]$ cd tests
[test@sms ~]$ ./configure --disable-all --enable-fftw
checking for a BSD-compatible install... /bin/install -c
checking whether build environment is sane... yes
...
----- SUMMARY -----
Package version..... : test-suite-1.3.0

Build user..... : ohpc-test
Build host..... : sms001
Configure date..... : 2017-03-24 15:41
Build architecture..... : aarch64
Compiler Families..... : gnu
MPI Families..... : mpich mvapich2 openmpi
Resource manager ..... : SLURM
Test suite configuration..... : short
...
Libraries:
  Adios ..... : disabled
  Boost ..... : disabled
  Boost MPI..... : disabled
  FFTW..... : enabled
  GSL..... : disabled
  HDF5..... : disabled
  HYPRE..... : disabled
...
```

Many OpenHPC components exist in multiple flavors to support multiple compiler and MPI runtime permutations, and the test suite takes this in to account by iterating through these combinations by default.

If `make check` is executed from the top-level test directory, all configured compiler and MPI permutations of a library will be exercised. The following highlights the execution of the FFTW related tests that were enabled in the previous step.

```
[test@sms ~]$ make check
make --no-print-directory check-TESTS
PASS: libs/fftw/ohpc-tests/test_mpi_families
=====
Testsuite summary for test-suite 1.3.0
=====
# TOTAL: 1
# PASS: 1
# SKIP: 0
# XFAIL: 0
# FAIL: 0
# XPASS: 0
# ERROR: 0
=====
[test@sms ~]$ cat libs/fftw/tests/family-gnu-*/rm_execution.log
1..3
ok 1 [libs/FFTW] Serial C binary runs under resource manager (SLURM/gnu/mpich)
ok 2 [libs/FFTW] MPI C binary runs under resource manager (SLURM/gnu/mpich)
ok 3 [libs/FFTW] Serial Fortran binary runs under resource manager (SLURM/gnu/mpich)
PASS rm_execution (exit status: 0)
1..3
ok 1 [libs/FFTW] Serial C binary runs under resource manager (SLURM/gnu/mvapich2)
ok 2 [libs/FFTW] MPI C binary runs under resource manager (SLURM/gnu/mvapich2)
ok 3 [libs/FFTW] Serial Fortran binary runs under resource manager (SLURM/gnu/mvapich2)
PASS rm_execution (exit status: 0)
1..3
ok 1 [libs/FFTW] Serial C binary runs under resource manager (SLURM/gnu/openmpi)
ok 2 [libs/FFTW] MPI C binary runs under resource manager (SLURM/gnu/openmpi)
ok 3 [libs/FFTW] Serial Fortran binary runs under resource manager (SLURM/gnu/openmpi)
PASS rm_execution (exit status: 0)
```

## D Customization

### D.1 Adding local Lmod modules to OpenHPC hierarchy

Locally installed applications can easily be integrated in to OpenHPC systems by following the Lmod convention laid out by the provided packages. Two sample module files are included in the `examples-ohpc` package—one representing an application with no compiler or MPI runtime dependencies, and one dependent on OpenMPI and the GNU toolchain. Simply copy these files to the prescribed locations, and the `lmod` application should pick them up automatically.

```
[sms]# mkdir /opt/ohpc/pub/modulefiles/example1
[sms]# cp /opt/ohpc/pub/examples/example.modulefile \
/opt/ohpc/pub/modulefiles/example1/1.0
[sms]# mkdir /opt/ohpc/pub/moduledeps/gnu7-openmpi/example2
[sms]# cp /opt/ohpc/pub/examples/example-mpi-dependent.modulefile \
/opt/ohpc/pub/moduledeps/gnu7-openmpi/example2/1.0
[sms]# module avail
```

```
----- /opt/ohpc/pub/moduledeps/gnu7-openmpi -----
adios/1.12.0  imb/4.1          netcdf/4.4.1.1  scalapack/2.0.2  slepc/3.7.4
boost/1.63.0  mpiP/3.4.1       petsc/3.7.6     scalasca/2.3.1  superlu_dist/4.2
example2/1.0  mumps/5.1.1      phdf5/1.10.1    scipy/0.19.1    tau/2.26.1
fftw/3.3.6    netcdf-cxx/4.3.0 pnetcdf/1.8.1   scorep/3.1      trilinos/12.10.1
hypre/2.11.2  netcdf-fortran/4.4.4 ptscotch/6.0.4  sionlib/1.7.1
```

```
----- /opt/ohpc/pub/moduledeps/gnu7 -----
R/3.4.1      metis/5.1.0      ocr/1.0.1       pdtoolkit/3.24  superlu/5.2.1
gsl/2.4      mpich/3.2         openblas/0.2.20  plasma/2.8.0
hdf5/1.10.1  numpy/1.13.1     openmpi/1.10.7 (L)  scotch/6.0.4
```

```
----- /opt/ohpc/pub/modulefiles -----
EasyBuild/3.3.1  example1/1.0  ohpc          (L)  valgrind/3.13.0
autotools        (L)  gnu7/7.1.0 (L)  papi/5.5.1
clustershell/1.7.3  hwloc/1.11.7  prun/1.1      (L)
cmake/3.9.1        llvm4/4.0.1   singularity/2.3.1
```

Where:  
L: Module is loaded

Use "module spider" to find all possible modules.  
Use "module keyword key1 key2 ..." to search for all possible modules matching any of the "keys".

## D.2 Rebuilding Packages from Source

Users of OpenHPC may find it desirable to rebuild one of the supplied packages to apply build customizations or satisfy local requirements. One way to accomplish this is to install the appropriate source RPM, modify the specfile as needed, and rebuild to obtain an updated binary RPM. A brief example using the FFTW library is highlighted below. Note that the source RPMs can be downloaded from the community build server at <https://build.openhpc.community> via a web browser or directly via `rpm` as highlighted below. The OpenHPC build system design leverages several keywords to control the choice of compiler and MPI families for relevant development libraries and the `rpmbuild` example illustrates how to override the default `mpi_family`.

```
# Install rpm-build package from base OS distro
[test@sms ~]$ sudo yum -y install rpm-build

# Install OpenHPC RPM build macros
[test@sms ~]$ sudo yum -y install ohpc-buildroot

# Download SRPM from OpenHPC repository and install locally
[test@sms ~]$ rpm -i \
  http://build.openhpc.community/OpenHPC:/1.3/CentOS_7.3/src/fftw-gnu-openmpi-ohpc-3.3.4-4.1.src.rpm

# Modify spec file as desired
[test@sms ~]$ cd ~/rpmbuild/SPECS
[test@sms ~rpmbuild/SPECS]$ perl -pi -e "s/enable-static=no/enable-static=yes/" fftw.spec

# Increment RPM release so package manager will see an update
[test@sms ~rpmbuild/SPECS]$ perl -pi -e "s/Release: 4.1/Release: 5.1/" fftw.spec

# Rebuild binary RPM. Note that additional directives can be specified to modify build
[test@sms ~rpmbuild/SPECS]$ rpmbuild -bb --define "mpi_family mvapich2" fftw.spec

# Install the new package
[test@sms ~]$ sudo yum -y install ~test/rpmbuild/RPMS/x86_64/fftw-gnu-mvapich2-ohpc-3.3.6-5.1.rpm
```

## E Package Manifest

This appendix provides a summary of available meta-package groupings and all of the individual RPM packages that are available as part of this OpenHPC release. The meta-packages provide a mechanism to group related collections of RPMs by functionality and provide a convenience mechanism for installation. A list of the available meta-packages and a brief description is presented in Table 1.

Table 1: Available OpenHPC Meta-packages

| Group Name                      | Description  |
|---------------------------------|--|
| ohpc-autotools                  | Collection of GNU autotools packages.  |
| ohpc-base                       | Collection of base packages.   |
| ohpc-base-compute               | Collection of compute node base packages.  |
| ohpc-ganglia                    | Collection of Ganglia monitoring and metrics packages.   |
| ohpc-gnu7-io-libs               | Collection of IO library builds for use with GNU compiler toolchain.                               |
| ohpc-gnu7-mpich-parallel-libs   | Collection of parallel library builds for use with GNU compiler toolchain and the MPICH runtime.   |
| ohpc-gnu7-openmpi-parallel-libs | Collection of parallel library builds for use with GNU compiler toolchain and the OpenMPI runtime. |
| ohpc-gnu7-parallel-libs         | Collection of parallel library builds for use with GNU compiler toolchain.                         |
| ohpc-gnu7-perf-tools            | Collection of performance tool builds for use with GNU compiler toolchain.                         |
| ohpc-gnu7-python-libs           | Collection of python related library builds for use with GNU compiler toolchain.                   |
| ohpc-gnu7-runtimes              | Collection of runtimes for use with GNU compiler toolchain.  |
| ohpc-gnu7-serial-libs           | Collection of serial library builds for use with GNU compiler toolchain.                           |
| ohpc-nagios                     | Collection of Nagios monitoring and metrics packages.  |
| ohpc-slurm-client               | Collection of client packages for SLURM.   |
| ohpc-slurm-server               | Collection of server packages for SLURM.   |
| ohpc-warewulf                   | Collection of base packages for Warewulf provisioning.   |

What follows next in this Appendix is a series of tables that summarize the underlying RPM packages available in this OpenHPC release. These packages are organized by groupings based on their general functionality and each table provides information for the specific RPM name, version, brief summary, and the web URL where additional information can be obtained for the component. Note that many of the 3rd party community libraries that are pre-packaged with OpenHPC are built using multiple compiler and MPI families. In these cases, the RPM package name includes delimiters identifying the development environment for which each package build is targeted. Additional information on the OpenHPC package naming scheme is presented in §5.6. The relevant package groupings and associated Table references are as follows:

- Administrative tools (Table 2)
- Provisioning (Table 3)
- Resource management (Table 4)
- Compiler families (Table 5)
- MPI families (Table 6)
- Development tools (Table 7)
- Performance analysis tools (Table 8)
- Distro support packages and dependencies (Table 9)
- IO Libraries (Table 10)
- Runtimes (Table 11)
- Serial Libraries (Table 12)
- Parallel Libraries (Table 13)

Table 2: **Administrative Tools**

| RPM Package Name                | Version | Info/URL   |
|---------------------------------|---------|--|
| clustershell-ohpc               | 1.7.3   | Python framework for efficient cluster administration.<br><a href="http://clustershell.sourceforge.net">http://clustershell.sourceforge.net</a>              |
| conman-ohpc                     | 0.2.8   | ConMan: The Console Manager.<br><a href="http://dun.github.io/conman">http://dun.github.io/conman</a>  |
| docs-ohpc                       | 1.3.2   | OpenHPC documentation.<br><a href="https://github.com/openhpc/ohpc">https://github.com/openhpc/ohpc</a>  |
| examples-ohpc                   | 1.4     | Example source code and templates for use within OpenHPC environment. <a href="https://github.com/openhpc/ohpc">https://github.com/openhpc/ohpc</a>          |
| ganglia-ohpc                    | 3.7.2   | Distributed Monitoring System.<br><a href="http://ganglia.sourceforge.net">http://ganglia.sourceforge.net</a>  |
| genders-ohpc                    | 1.22    | Static cluster configuration database.<br><a href="https://github.com/chaos/genders">https://github.com/chaos/genders</a>                                    |
| lmod-defaults-gnu-mpich-ohpc    | 1.2     | OpenHPC default login environments.<br><a href="https://github.com/openhpc/ohpc">https://github.com/openhpc/ohpc</a>   |
| lmod-defaults-gnu-openmpi-ohpc  |         |  |
| lmod-defaults-gnu7-mpich-ohpc   | 1.3.1   |  |
| lmod-defaults-gnu7-openmpi-ohpc |         |  |
| lmod-ohpc                       | 7.6.1   | Lua based Modules (lmod).<br><a href="https://github.com/TACC/Lmod">https://github.com/TACC/Lmod</a>   |
| losf-ohpc                       | 0.54.0  | A Linux operating system framework for managing HPC clusters. <a href="https://github.com/hpcsi/losf">https://github.com/hpcsi/losf</a>                      |
| mrsh-ohpc                       | 2.12    | Remote shell program that uses munge authentication.<br>None   |
| nagios-plugins-ohpc             | 2.2.0   | Host/service/network monitoring program plugins for Nagios.<br><a href="https://www.nagios-plugins.org">https://www.nagios-plugins.org</a>                   |
| nagios-ohpc                     | 4.3.1   | Host/service/network monitoring program.<br><a href="http://www.nagios.org">http://www.nagios.org</a>  |
| ndoutils-ohpc                   | 2.1.3   | Stores all configuration and event data from Nagios in a database. <a href="http://www.nagios.org/download/addons">http://www.nagios.org/download/addons</a> |
| nrpe-ohpc                       | 3.1.0   | Host/service/network monitoring agent for Nagios.<br><a href="http://www.nagios.org">http://www.nagios.org</a>   |
| ohpc-release                    | 1.3     | OpenHPC release files.<br><a href="https://github.com/openhpc/ohpc">https://github.com/openhpc/ohpc</a>  |
| pdsh-ohpc                       | 2.33    | Parallel remote shell program.<br><a href="http://sourceforge.net/projects/pdsh">http://sourceforge.net/projects/pdsh</a>                                    |
| prun-ohpc                       | 1.1     | Convenience utility for parallel job launch.<br><a href="https://github.com/openhpc/ohpc">https://github.com/openhpc/ohpc</a>                                |
| test-suite-ohpc                 | 1.3.2   | Integration test suite for OpenHPC.<br><a href="https://github.com/openhpc/ohpc/tests">https://github.com/openhpc/ohpc/tests</a>                             |

Table 3: **Provisioning**

| RPM Package Name               | Version | Info/URL  |
|--------------------------------|---------|---|
| warewulf-common-ohpc           | 3.7pre  | A suite of tools for clustering.<br><a href="http://warewulf.lbl.gov">http://warewulf.lbl.gov</a>         |
| warewulf-ipmi-ohpc             | 3.7pre  | IPMI Module for Warewulf.<br><a href="http://warewulf.lbl.gov">http://warewulf.lbl.gov</a>                |
| warewulf-cluster-node-ohpc     | 3.7pre  | Tools used for clustering with Warewulf.<br><a href="http://warewulf.lbl.gov">http://warewulf.lbl.gov</a> |
| warewulf-cluster-ohpc          | 3.7pre  | Tools used for clustering with Warewulf.<br><a href="http://warewulf.lbl.gov">http://warewulf.lbl.gov</a> |
| warewulf-vnfs-ohpc             | 3.7pre  | Warewulf VNFS Module.<br><a href="http://warewulf.lbl.gov">http://warewulf.lbl.gov</a>                    |
| warewulf-provision-ohpc        | 3.7pre  | Warewulf - Provisioning Module.<br><a href="http://warewulf.lbl.gov">http://warewulf.lbl.gov</a>          |
| warewulf-provision-server-ohpc | 3.7pre  | Warewulf - Provisioning Module - Server.<br><a href="http://warewulf.lbl.gov">http://warewulf.lbl.gov</a> |

Table 4: **Resource Management**

| RPM Package Name     | Version | Info/URL   |
|----------------------|---------|--|
| munge-ohpc           | 0.5.12  | MUNGE authentication service.<br><a href="http://dun.github.io/munge">http://dun.github.io/munge</a>                               |
| slurm-devel-ohpc     | 17.02.7 | Development package for Slurm.<br><a href="https://slurm.schedmd.com">https://slurm.schedmd.com</a>                                |
| slurm-pam_slurm-ohpc | 17.02.7 | PAM module for restricting access to compute nodes via Slurm. <a href="https://slurm.schedmd.com">https://slurm.schedmd.com</a>    |
| slurm-perlapi-ohpc   | 17.02.7 | Perl API to Slurm.<br><a href="https://slurm.schedmd.com">https://slurm.schedmd.com</a>  |
| slurm-contribs-ohpc  | 17.02.7 | Perl tool to print Slurm job state information.<br><a href="https://slurm.schedmd.com">https://slurm.schedmd.com</a>               |
| slurm-sql-ohpc       | 17.02.7 | Slurm SQL support.<br><a href="https://slurm.schedmd.com">https://slurm.schedmd.com</a>  |
| slurm-ohpc           | 17.02.7 | Slurm Workload Manager.<br><a href="https://slurm.schedmd.com">https://slurm.schedmd.com</a>                                       |
| slurm-munge-ohpc     | 17.02.7 | Slurm authentication and crypto implementation using Munge.<br><a href="https://slurm.schedmd.com">https://slurm.schedmd.com</a>   |
| slurm-slurmdbd-ohpc  | 17.02.7 | Slurm database daemon.<br><a href="https://slurm.schedmd.com">https://slurm.schedmd.com</a>  |
| slurm-plugins-ohpc   | 17.02.7 | Slurm plugins (loadable shared objects).<br><a href="https://slurm.schedmd.com">https://slurm.schedmd.com</a>                      |
| slurm-torque-ohpc    | 17.02.7 | Torque/PBS wrappers for transition from Torque/PBS to Slurm.<br><a href="https://slurm.schedmd.com">https://slurm.schedmd.com</a>  |
| slurm-openlava-ohpc  | 17.02.7 | openlava/LSF wrappers for transition from OpenLava/LSF to Slurm. <a href="https://slurm.schedmd.com">https://slurm.schedmd.com</a> |

Table 5: **Compiler Families**

| RPM Package Name     | Version | Info/URL   |
|----------------------|---------|--|
| gnu-compilers-ohpc   | 5.4.0   | The GNU C Compiler and Support Files.<br><a href="http://gcc.gnu.org">http://gcc.gnu.org</a> |
| gnu7-compilers-ohpc  | 7.1.0   | The GNU C Compiler and Support Files.<br><a href="http://gcc.gnu.org">http://gcc.gnu.org</a> |
| llvm4-compilers-ohpc | 4.0.1   | The LLVM Compiler Infrastructure.<br><a href="http://www.llvm.org">http://www.llvm.org</a>   |

Table 6: **MPI Families**

| RPM Package Name  | Version | Info/URL   |
|-------------------|---------|--|
| mpich-gnu-ohpc    | 3.2     | MPICH MPI implementation.<br><a href="http://www.mpich.org">http://www.mpich.org</a>               |
| mpich-gnu7-ohpc   |         |  |
| openmpi-gnu-ohpc  | 1.10.6  | A powerful implementation of MPI.<br><a href="http://www.open-mpi.org">http://www.open-mpi.org</a> |
| openmpi-gnu7-ohpc | 1.10.7  |  |

Table 7: **Development Tools**

| RPM Package Name               | Version | Info/URL  |
|--------------------------------|---------|---|
| EasyBuild-ohpc                 | 3.3.1   | Build and installation framework.<br><a href="http://hpcugent.github.com/easybuild">http://hpcugent.github.com/easybuild</a>                                |
| automake-ohpc                  | 1.15    | A GNU tool for automatically creating Makefiles.<br><a href="http://www.gnu.org/software/automake">http://www.gnu.org/software/automake</a>                 |
| autoconf-ohpc                  | 2.69    | A GNU tool for automatically configuring source code.<br><a href="http://www.gnu.org/software/autoconf">http://www.gnu.org/software/autoconf</a>            |
| cmake-ohpc                     | 3.9.1   | CMake is an open-source, cross-platform family of tools designed to build, test and package software. <a href="https://cmake.org">https://cmake.org</a>     |
| hwloc-ohpc                     | 1.11.7  | Portable Hardware Locality.<br><a href="http://www.open-mpi.org/projects/hwloc">http://www.open-mpi.org/projects/hwloc</a>                                  |
| libtool-ohpc                   | 2.4.6   | The GNU Portable Library Tool.<br><a href="http://www.gnu.org/software/libtool">http://www.gnu.org/software/libtool</a>                                     |
| python-scipy-gnu-mpich-ohpc    | 0.19.0  | Scientific Tools for Python.<br><a href="http://www.scipy.org">http://www.scipy.org</a>   |
| python-scipy-gnu-openmpi-ohpc  |         |   |
| python-scipy-gnu7-mpich-ohpc   | 0.19.1  |   |
| python-scipy-gnu7-openmpi-ohpc |         |   |
| python-numpy-gnu-ohpc          | 1.11.1  | NumPy array processing for numbers, strings, records and objects. <a href="http://sourceforge.net/projects/numpy">http://sourceforge.net/projects/numpy</a> |
| python-numpy-gnu7-ohpc         | 1.13.1  |   |
| spack-ohpc                     | 0.10.0  | HPC software package management.<br><a href="https://github.com/LLNL/spack">https://github.com/LLNL/spack</a>   |
| valgrind-ohpc                  | 3.13.0  | Valgrind Memory Debugger.<br><a href="http://www.valgrind.org">http://www.valgrind.org</a>  |

Table 8: Performance Analysis Tools

| RPM Package Name   | Version | Info/URL  |
|--|---------|---|
| imb-gnu-mpich-ohpc<br>imb-gnu-openmpi-ohpc<br>imb-gnu7-mpich-ohpc<br>imb-gnu7-openmpi-ohpc                     | 4.1     | Intel MPI Benchmarks (IMB).<br><a href="https://software.intel.com/en-us/articles/intel-mpi-benchmarks">https://software.intel.com/en-us/articles/intel-mpi-benchmarks</a>  |
| mpiP-gnu-mpich-ohpc<br>mpiP-gnu-openmpi-ohpc<br>mpiP-gnu7-mpich-ohpc<br>mpiP-gnu7-openmpi-ohpc                 | 3.4.1   | mpiP: a lightweight profiling library for MPI applications.<br><a href="http://mpip.sourceforge.net">http://mpip.sourceforge.net</a>  |
| papi-ohpc  | 5.5.1   | Performance Application Programming Interface.<br><a href="http://icl.cs.utk.edu/papi">http://icl.cs.utk.edu/papi</a>   |
| pdtoolkit-gnu-ohpc   | 3.23    | PDT is a framework for analyzing source code.<br><a href="http://www.cs.uoregon.edu/Research/pdt">http://www.cs.uoregon.edu/Research/pdt</a>  |
| pdtoolkit-gnu7-ohpc  | 3.24    |   |
| scalasca-gnu-mpich-ohpc<br>scalasca-gnu-openmpi-ohpc<br>scalasca-gnu7-mpich-ohpc<br>scalasca-gnu7-openmpi-ohpc | 2.3.1   | Toolset for performance analysis of large-scale parallel applications.<br><a href="http://www.scalasca.org">http://www.scalasca.org</a>   |
| scorep-gnu-mpich-ohpc<br>scorep-gnu-openmpi-ohpc   | 3.0     | Scalable Performance Measurement Infrastructure for Parallel Codes.<br><a href="http://www.vi-hps.org/projects/score-p">http://www.vi-hps.org/projects/score-p</a>  |
| scorep-gnu7-mpich-ohpc<br>scorep-gnu7-openmpi-ohpc   | 3.1     |   |
| sionlib-gnu-mpich-ohpc<br>sionlib-gnu-openmpi-ohpc   | 1.7.0   | Scalable Performance Measurement Infrastructure for Parallel Codes. <a href="http://www.fz-juelich.de/ias/jsc/EN/Expertise/Support/Software/SIONlib/_node.html">http://www.fz-juelich.de/ias/jsc/EN/Expertise/Support/Software/SIONlib/_node.html</a> |
| tau-gnu-mpich-ohpc<br>tau-gnu-openmpi-ohpc<br>tau-gnu7-mpich-ohpc<br>tau-gnu7-openmpi-ohpc                     | 2.26.1  | Tuning and Analysis Utilities Profiling Package.<br><a href="http://www.cs.uoregon.edu/research/tau/home.php">http://www.cs.uoregon.edu/research/tau/home.php</a>   |

Table 9: Distro Support Packages/Dependencies

| RPM Package Name    | Version | Info/URL  |
|---------------------|---------|---|
| lua-bit-ohpc        | 1.0.2   | Module for Lua which adds bitwise operations on numbers.<br><a href="http://bitop.luajit.org">http://bitop.luajit.org</a>                                 |
| lua-filesystem-ohpc | 1.6.3   | Lua library to Access Directories and Files.<br><a href="http://keplerproject.github.com/luafilesystem">http://keplerproject.github.com/luafilesystem</a> |
| lua-posix-ohpc      | 33.2.1  | POSIX library for Lua.<br><a href="https://github.com/luaposition/luaposition">https://github.com/luaposition/luaposition</a>                             |

Table 10: IO Libraries

| RPM Package Name   | Version | Info/URL   |   |
|--|---------|--|---|
| adios-gnu-mpich-ohpc<br>adios-gnu-openmpi-ohpc   | 1.11.0  | The Adaptable IO System (ADIOS).<br><a href="http://www.olcf.ornl.gov/center-projects/adios">http://www.olcf.ornl.gov/center-projects/adios</a>  |   |
| adios-gnu7-mpich-ohpc<br>adios-gnu7-openmpi-ohpc   | 1.12.0  |  |   |
| hdf5-gnu-ohpc  | 1.8.17  | A general purpose library and file format for storing scientific data. <a href="http://www.hdfgroup.org/HDF5">http://www.hdfgroup.org/HDF5</a>   |   |
| hdf5-gnu7-ohpc   | 1.10.1  |  |   |
| netcdf-cxx-gnu-mpich-ohpc<br>netcdf-cxx-gnu-openmpi-ohpc<br>netcdf-cxx-gnu7-mpich-ohpc<br>netcdf-cxx-gnu7-openmpi-ohpc                 | 4.3.0   | C++ Libraries for the Unidata network Common Data Form.<br><a href="http://www.unidata.ucar.edu/software/netcdf">http://www.unidata.ucar.edu/software/netcdf</a>   |   |
| netcdf-gnu-mpich-ohpc<br>netcdf-gnu-openmpi-ohpc<br>netcdf-gnu7-mpich-ohpc<br>netcdf-gnu7-openmpi-ohpc                                 | 4.4.1.1 | C Libraries for the Unidata network Common Data Form.<br><a href="http://www.unidata.ucar.edu/software/netcdf">http://www.unidata.ucar.edu/software/netcdf</a>   |   |
| netcdf-fortran-gnu-mpich-ohpc<br>netcdf-fortran-gnu-openmpi-ohpc<br>netcdf-fortran-gnu7-mpich-ohpc<br>netcdf-fortran-gnu7-openmpi-ohpc | 4.4.4   |  |   |
| phdf5-gnu-mpich-ohpc<br>phdf5-gnu-openmpi-ohpc   | 1.8.17  |  | A general purpose library and file format for storing scientific data.<br><a href="http://www.hdfgroup.org/HDF5">http://www.hdfgroup.org/HDF5</a> |
| phdf5-gnu7-mpich-ohpc<br>phdf5-gnu7-openmpi-ohpc   | 1.10.1  |  |   |
| pnetcdf-gnu7-mpich-ohpc<br>pnetcdf-gnu7-openmpi-ohpc   | 1.8.1   | A Parallel NetCDF library (PnetCDF).<br><a href="http://cucis.ece.northwestern.edu/projects/PnetCDF">http://cucis.ece.northwestern.edu/projects/PnetCDF</a>  |   |
| sionlib-gnu7-mpich-ohpc<br>sionlib-gnu7-openmpi-ohpc   | 1.7.1   | Scalable I/O Library for Parallel Access to Task-Local Files.<br><a href="http://www.fz-juelich.de/ias/jsc/EN/Expertise/Support/Software/SIONlib/_node.html">http://www.fz-juelich.de/ias/jsc/EN/Expertise/Support/Software/SIONlib/_node.html</a> |   |

Table 11: **Runtimes**

| RPM Package Name              | Version | Info/URL   |
|-------------------------------|---------|--|
| ocr-gnu-ohpc<br>ocr-gnu7-ohpc | 1.0.1   | Open Community Runtime (OCR) for shared memory.<br><a href="https://xstack.exascale-tech.com/wiki">https://xstack.exascale-tech.com/wiki</a> |
| singularity-ohpc              | 2.3.1   | Application and environment virtualization.<br><a href="http://singularity.lbl.gov">http://singularity.lbl.gov</a>                           |

Table 12: **Serial Libraries**

| RPM Package Name                      | Version | Info/URL  |
|---------------------------------------|---------|---|
| R-gnu7-ohpc                           | 3.4.1   | R is a language and environment for statistical computing and graphics (S-Plus like). <a href="http://www.r-project.org">http://www.r-project.org</a>                                     |
| gsl-gnu-ohpc                          | 2.2.1   | GNU Scientific Library (GSL).<br><a href="http://www.gnu.org/software/gsl">http://www.gnu.org/software/gsl</a>  |
| gsl-gnu7-ohpc                         | 2.4     |   |
| metis-gnu-ohpc<br>metis-gnu7-ohpc     | 5.1.0   | Serial Graph Partitioning and Fill-reducing Matrix Ordering.<br><a href="http://glaros.dtc.umn.edu/gkhome/metis/metis/overview">http://glaros.dtc.umn.edu/gkhome/metis/metis/overview</a> |
| openblas-gnu-ohpc                     | 0.2.19  | An optimized BLAS library based on GotoBLAS2.<br><a href="http://www.openblas.net">http://www.openblas.net</a>  |
| openblas-gnu7-ohpc                    | 0.2.20  |   |
| plasma-gnu7-ohpc                      | 2.8.0   | Parallel Linear Algebra Software for Multicore Architectures.<br><a href="https://bitbucket.org/icl/plasma">https://bitbucket.org/icl/plasma</a>  |
| scotch-gnu7-ohpc                      | 6.0.4   | Graph, mesh and hypergraph partitioning library.<br><a href="http://www.labri.fr/perso/pelegrin/scotch">http://www.labri.fr/perso/pelegrin/scotch</a>                                     |
| superlu-gnu-ohpc<br>superlu-gnu7-ohpc | 5.2.1   | A general purpose library for the direct solution of linear equations. <a href="http://crd.lbl.gov/~xiaoye/SuperLU">http://crd.lbl.gov/~xiaoye/SuperLU</a>                                |

Table 13: **Parallel Libraries**

| RPM Package Name   | Version | Info/URL  |
|--|---------|---|
| boost-gnu-mpich-ohpc<br>boost-gnu-openmpi-ohpc<br>boost-gnu7-mpich-ohpc<br>boost-gnu7-openmpi-ohpc                             | 1.63.0  | Boost free peer-reviewed portable C++ source libraries.<br><a href="http://www.boost.org">http://www.boost.org</a>  |
| fftw-gnu-mpich-ohpc<br>fftw-gnu-openmpi-ohpc   | 3.3.4   | A Fast Fourier Transform library.<br><a href="http://www.fftw.org">http://www.fftw.org</a>  |
| fftw-gnu7-mpich-ohpc<br>fftw-gnu7-openmpi-ohpc   | 3.3.6   |   |
| hypre-gnu-mpich-ohpc<br>hypre-gnu-openmpi-ohpc   | 2.11.1  | Scalable algorithms for solving linear systems of equations.<br><a href="http://www.llnl.gov/casc/hypre">http://www.llnl.gov/casc/hypre</a>                                 |
| hypre-gnu7-mpich-ohpc<br>hypre-gnu7-openmpi-ohpc   | 2.11.2  |   |
| mumps-gnu-mpich-ohpc<br>mumps-gnu-openmpi-ohpc   | 5.0.2   | A MULTifrontal Massively Parallel Sparse direct Solver.<br><a href="http://mumps.enseeiht.fr">http://mumps.enseeiht.fr</a>  |
| mumps-gnu7-mpich-ohpc<br>mumps-gnu7-openmpi-ohpc   | 5.1.1   |   |
| petsc-gnu-mpich-ohpc<br>petsc-gnu-openmpi-ohpc   | 3.7.5   | Portable Extensible Toolkit for Scientific Computation.<br><a href="http://www.mcs.anl.gov/petsc">http://www.mcs.anl.gov/petsc</a>  |
| petsc-gnu7-mpich-ohpc<br>petsc-gnu7-openmpi-ohpc   | 3.7.6   |   |
| ptscotch-gnu-mpich-ohpc<br>ptscotch-gnu7-openmpi-ohpc  | 6.0.4   | Graph, mesh and hypergraph partitioning library using MPI.<br><a href="http://www.labri.fr/perso/pelegrin/scotch">http://www.labri.fr/perso/pelegrin/scotch</a>             |
| slepc-gnu7-mpich-ohpc<br>slepc-gnu7-openmpi-ohpc   | 3.7.4   | A library for solving large scale sparse eigenvalue problems.<br><a href="http://www.grycap.upv.es/slepc">http://www.grycap.upv.es/slepc</a>                                |
| superlu_dist-gnu-mpich-ohpc<br>superlu_dist-gnu-openmpi-ohpc<br>superlu_dist-gnu7-mpich-ohpc<br>superlu_dist-gnu7-openmpi-ohpc | 4.2     | A general purpose library for the direct solution of linear equations.<br><a href="http://crd-legacy.lbl.gov/~xiaoye/SuperLU">http://crd-legacy.lbl.gov/~xiaoye/SuperLU</a> |
| trilinos-gnu-mpich-ohpc<br>trilinos-gnu-openmpi-ohpc<br>trilinos-gnu7-mpich-ohpc<br>trilinos-gnu7-openmpi-ohpc                 | 12.10.1 | A collection of libraries of numerical algorithms.<br><a href="http://trilinos.sandia.gov/index.html">http://trilinos.sandia.gov/index.html</a>                             |

## F Package Signatures

All of the RPMs provided via the OpenHPC repository are signed with a GPG signature. By default, the underlying package managers will verify these signatures during installation to ensure that packages have not been altered. The RPMs can also be manually verified and the public signing key fingerprint for the latest repository is shown below:

Fingerprint: DD5D 8CAA CB57 364F FCC2 D3AE C468 07FF **26CE 6884**

The following command can be used to verify an RPM once it has been downloaded locally by confirming if the package is signed, and if so, indicating which key was used to sign it. The example below highlights usage for a local copy of the `docs-ohpc` package and illustrates how the *key ID* matches the fingerprint shown above.

```
[sms]# rpm --checksig -v docs-ohpc-*.rpm
docs-ohpc-1.0-1.1.x86_64.rpm:
  Header V3 RSA/SHA256 Signature, key ID 26ce6884: OK
  Header SHA1 digest: OK (c3873bf495c51d2ea6d3ef23ab88be105983c72c)
  V3 RSA/SHA256 Signature, key ID 26ce6884: OK
  MD5 digest: OK (43d067f33fb370e30a39789439ead238)
```